



LS3/5A

This monitor speaker was designed to suit environments where monitoring on headphones is unsatisfactory and yet where there is insufficient room for a grade 1 monitor.

It is manufactured by licencees to the highest and most exacting standards using the finest materials available. It surpasses all expectations of a monitor speaker so compact and has become an 'industry standard' in radio and television studios throughout the world. Its low colouration, smooth frequency response and excellent stereo imaging make it suitable for a variety of applications where compactness or portability are essential.

Frequency response

70Hz to 20kHz +/- 3dB.

Impedance

12 ohms nominal.

Sensitivity at 1m for 2.83 volts input.

82.dB.

Maximum sound pressure level (pair at 1.5m.)

95.dBA.

Power Handling - Continuous programme

30 watts related to 12 ohm

Drive unit - Bass/Midrange

110mm Bextrene.

Drive unit - H.F.

19mm modified synthetic dome.

Crossover

13 precision elements

Crossover frequency

3kHz.

Bass loading

Infinite Baffle.

Speaker connectors

Male XLR - 3

Cabinet

Birch plywood critically damped to specification CT4/10A

Finishes

Selected wood veneers in Teak, Walnut and Black Ash.

Dimensions

-Height

300mm (12")

-Width

185 (7.5")

-Depth

160mm (6")

Weight

5.5kg net. (11.5lbs) each.